

YOUR HOSE ASSEMBLY MACHINE SUPPLIER



WWW.DHYDRO.COM

Wahlforssinkatu 10 - 80100 Joensuu - Finland - Tel. +358 13 120 490 - info@dhydro.com

SM 625 E



TECHNICAL SPECIFICATIONS

Max hose size	1" 4SH, 1¼" 2SN
Crimping force (kN):	1100
Max crimping diameter:	61 mm
Max opening:	die diameter + 10 mm
Control	Micrometer
Master dies opening / Length(mm):	85/66
Crimping range (mm):	6 mm – 61 mm
Weight (kg)	29
Dimensions (LxWxH mm)	285 x 210 x 340

STANDARD DIE SETS

	Range (mm)	Lenght
25-06	6-16	40
25-08	8-18	40
25-11	11-21	40
25-14	14-24	40
25-17	17-27	40
25-20	20-30	45
25-23	23-33	50
25-26	26-36	50
25-31	31-41	55
25-34	34-44	60
25-39	39-49	60
25-43	43-53	65
25-45	45-55	65
25-51*	51-61	65

* Max. ferrule diameter before crimping 61 mm

MICROMETER



WWW.DHYDRO.COM

Wahlforssinkatu 10 - 80100 Joensuu - Finland - Tel. +358 13 120 490 - info@dhydro.com

SM 625



TECHNICAL SPECIFICATIONS

Max hose size	1" 4SP, 1¼" 2SN
Crimping force (kN):	1100
Max crimping diameter:	61 mm
Max opening:	die diameter + 10 mm
Control	Manometer
Master dies opening / Length(mm):	85/66
Crimping range (mm):	6 mm – 61 mm
Weight (kg)	29
Dimensions (LxWxH mm)	285 x 210 x 340

STANDARD DIE SETS


	Range (mm)	Lenght
25-06	6-16	40
25-08	8-18	40
25-11	11-21	40
25-14	14-24	40
25-17	17-27	40
25-20	20-30	45
25-23	23-33	50
25-26	26-36	50
25-31	31-41	55
25-34	34-44	60
25-39	39-49	60
25-43	43-53	65
25-45	45-55	65
25-51*	51-61	65

* Max. ferrule diameter before crimping 61 mm

WWW.DHYDRO.COM

Wahlforssinkatu 10 - 80100 Joensuu - Finland - Tel. +358 13 120 490 - info@dhydro.com

SM 25 HP/AP



TECHNICAL SPECIFICATIONS

Max hose size	1" 4 SH, 1 1/2"
Crimping force (kN):	1200
Max ferrule diameter (mm):	61
Max opening diameter (mm):	die diameter + 23
Actuation / HP model:	Two-speed hand pump
Actuation / AP model:	Air pressure
Control:	Micrometer with led
Master dies opening / Length (mm):	98/64,5
Crimping range (mm):	6 – 61
Crimping unit weight (kg):	25
Crimping unit dimensions (LxWxH mm)	230 x 200 x 275

STANDARD DIE SETS

	Range (mm)	Lenght
38-06	6-16	45
38-08	8-18	45
38-11	11-21	45
38-14	14-24	45
38-17	17-27	45
38-20	20-30	55
38-23	23-33	55
38-26	26-36	55
38-30S	30-40	60
38-34S	34-44	60
38-39S	39-49	65
38-45S	45-55	65
38-51S*	51-61	65

* Max. ferrule diameter before crimping 61 mm


HAND PUMP / AIR PUMP



WWW.DHYDRO.COM

Wahlforssinkatu 10 - 80100 Joensuu - Finland - Tel. +358 13 120 490 - info@dhydro.com

SM 25L HP/AP



TECHNICAL SPECIFICATIONS

Max hose size	1" 4 SH, 1 1/2"
Crimping force (kN):	1200
Max ferrule diameter (mm):	61
Max opening diameter (mm):	die diameter + 15
Actuation / HP model:	Two-speed hand pump
Actuation / AP model	Air pressure
Control :	Micrometer with led
Master dies opening / Length (mm):	90/64,5
Crimping range (mm):	6 – 61
Crimping unit weight (kg)	25
Crimping unit dimensions (LxWxH mm)	230 x 200 x 275

STANDARD DIE SETS

	Range (mm)	Lenght
38-06	6-16	45
38-08	8-18	45
38-11	11-21	45
38-14	14-24	45
38-17	17-27	45
38-20	20-30	55
38-23	23-33	55
38-26	26-36	55
38-30S	30-40	60
38-34S	34-44	60
38-39S	39-49	65
38-45S	45-55	65
38-51S*	51-61	65

* Max. ferrule diameter before crimping 61 mm


HAND PUMP / AIR PUMP



WWW.DHYDRO.COM

Wahlforssinkatu 10 - 80100 Joensuu - Finland - Tel. +358 13 120 490 - info@dhydro.com

SM 25L AC



STANDARD DIE SETS

	Range (mm)	Lenght
38-06	6-16	45
38-08	8-18	45
38-11	11-21	45
38-14	14-24	45
38-17	17-27	45
38-20	20-30	55
38-23	23-33	55
38-26	26-36	55
38-30S	30-40	60
38-34S	34-44	60
38-39S	39-49	65
38-45S	45-55	65
38-51S*	51-61	65

* Max. ferrule diameter before crimping 61 mm

TECHNICAL SPECIFICATIONS

Max hose size	1" 4 SH, 1 1/2"
Crimping force (kN):	1200
Max crimping diameter (mm):	61
Max opening diameter (mm):	die diameter + 15
Motor:	0.37 kW 230V 1ph 50Hz
Possible to operate with 12V or 24V inverter	
Control :	Micrometer
Master dies opening / Length (mm):	90/64,5
Crimping range (mm):	6 – 61
Weight (kg)	55
Dimensions (LxWxH mm)	630 x 330 x 410

WWW.DHYDRO.COM

Wahlforssinkatu 10 - 80100 Joensuu - Finland - Tel. +358 13 120 490 - info@dhydro.com

SM 32 M



STANDARD DIE SETS

	RANGE (mm)	LENGHT
32-06	6-16	40
32-08	8-18	40
32-11	11-21	40
32-14	14-24	40
32-17	17-27	40
32-20	20-30	45
32-23	23-33	50
32-26	26-36	50
32-31	31-41	55
32-34	34-44	60
32-39	39-49	60
32-43	43-53	65
32-45	45-55	65
32-51*	51-61	65

* Max. ferrule diameter before crimping 61 mm

TECHNICAL SPECIFICATIONS

Max hose size	1 1/2" 1SN, 1 1/4" 2SN, 1" 4SP
Crimping force (kN):	1450
Max crimping Ø (mm):	61
Max opening (mm):	die diameter + 20
Standard motor:	2,2 kW 400V 3-Ph
Different voltage versions available	
Control	Micrometer
Master dies opening / Length(mm):	95/66
Crimping range (mm):	6 – 61
Weight (kg)	94 (without oil)
Dimensions (LxWxH mm)	710 x 360 x 600
Quick Change-set	Optional
Stand for machine	Optional

OPTIONS



Quick Change
Set: including
storage rack &
handle



Solid stand with ability to mount
the Quick Change set and
machine

WWW.DHYDRO.COM

Wahlforssinkatu 10 - 80100 Joensuu - Finland - Tel. +358 13 120 490 - info@dhydro.com

SM 32 MC



STANDARD DIE SETS

	RANGE (mm)	LENGHT
32-06	6-16	40
32-08	8-18	40
32-11	11-21	40
32-14	14-24	40
32-17	17-27	40
32-20	20-30	45
32-23	23-33	50
32-26	26-36	50
32-31	31-41	55
32-34	34-44	60
32-39	39-49	60
32-43	43-53	65
32-45	45-55	65
32-51*	51-61	65

* Max. ferrule diameter before crimping 61 mm


TECHNICAL SPECIFICATIONS

Max hose size	1 1/2" 1SN, 1 1/4" 2SN, 1" 4SP
Crimping force (kN):	1450
Max crimping Ø (mm):	61
Max opening (mm):	die diameter + 20
Standard motor:	2,2kW 400V 3-Ph
Different voltage versions available	
Control	Manual vernier
Master dies opening / Length(mm):	95/66
Crimping range (mm):	6 – 61
Weight (kg)	110 (without oil)
Dimensions (LxWxH mm)	640 x 430 x 590
Quick Change-set	Optional
Stand for machine	Optional

OPTIONS



Quick Change Set: including storage rack & handle



Solid stand with ability to mount the Quick Change set and machine

WWW.DHYDRO.COM

Wahlforssinkatu 10 - 80100 Joensuu - Finland - Tel. +358 13 120 490 - info@dhydro.com

SM 38 M



STANDARD DIE SETS

	Range (mm)	Lenght
38-06	6-16	45
38-08	8-18	45
38-11	11-21	45
38-14	14-24	45
38-17	17-27	45
38-20	20-30	55
38-23	23-33	55
38-26	26-36	55
38-30	30-40	75
38-34	34-44	75
38-39	39-49	85
38-45	45-55	85
38-51*	51-61	85

TECHNICAL SPECIFICATIONS


*Max. ferrule diameter before crimping 61 mm

Max hose size	1 1/2" 2 SN, 1 1/4" 4 SH
Crimping force (kN):	1650
Max crimping Ø (mm):	61
Max opening (mm):	die diameter + 32
Standard motor:	2.2 kW 400V 3-Ph
Control	Micrometer
Master dies opening / Length(mm):	105/105
Crimping range (mm):	6 – 61
Weight (kg)	136 (without oil)
Dimensions (LxWxH mm)	710 x 440 x 650
Quick Change-set	Optional
Stand for machine	Optional

OPTIONS



Quick Change Set: including storage rack & handle



Solid stand with ability to mount the Quick Change set and machine

WWW.DHYDRO.COM

Wahlforssinkatu 10 - 80100 Joensuu - Finland - Tel. +358 13 120 490 - info@dhydro.com

SM 38 EC/SC



STANDARD DIE SETS

	Range (mm)	Length
38-06	6-16	45
38-08	8-18	45
38-11	11-21	45
38-14	14-24	45
38-17	17-27	45
38-20	20-30	55
38-23	23-33	55
38-26	26-36	55
38-30	30-40	75
38-34	34-44	75
38-39	39-49	85
38-45	45-55	85
38-51*	51-61	85

* Max. ferrule diameter before crimping 61 mm


TECHNICAL SPECIFICATIONS

Max hose size	1 1/2" 2 SN, 1 1/4" 4SH
Crimping force (kN):	1650
Max crimping Ø (mm):	61
Max opening (mm):	die diameter + 32
Standard motor:	4 kW 400V 3-Ph
Different voltage versions available	
Control	Digital EC control Advanced digital SC control
Master dies opening / Length(mm):	105/105
Crimping range (mm):	6 – 61
Weight (kg)	157 (without oil)
Dimensions (LxWxH mm)	640 x 565 x 640
Quick Change-set	Optional
Foot pedal	Optional (only for SC version)
Stand for machine	Optional


OPTIONS



Quick Change
Set: including
storage rack &
handle



Solid stand with ability to mount
the Quick Change set and
machine




Foot pedal only for SC version

WWW.DHYDRO.COM

Wahlforssinkatu 10 - 80100 Joensuu - Finland - Tel. +358 13 120 490 - info@dhydro.com

SM 50 M



STANDARD DIE SETS

	Range (mm)	Lenght
38-06	6-16	45
38-08	8-18	45
38-11	11-21	45
38-14	14-24	45
38-17	17-27	45
38-20	20-30	55
38-23	23-33	55
38-26	26-36	55
38-30	30-40	75
38-34	34-44	75
38-39	39-49	85
38-45	45-55	85
38-51	51-61	85
38-57	57-67	90
38-63	63-73	90
38-67	67-77	90
With master dies	75-85	105

TECHNICAL SPECIFICATIONS

Max hose size	2" 2 SN, 1 1/2" 4 SH
Crimping force (kN):	1800
Max crimping Ø (mm):	85
Max opening (mm):	die diameter + 32
Standard motor:	3 kW 400V 3-Ph
Control	Micrometer
Master dies opening / Length(mm):	107/105
Crimping range (mm):	6 – 85
Weight (kg)	148 (without oil)
Dimensions (LxWxH mm)	710 x 440 x 650
Quick Change-set	Optional
Stand for machine	Optional

OPTIONS



Quick Change Set: including storage rack & handle



Solid stand with ability to mount the Quick Change set and machine

WWW.DHYDRO.COM

Wahlforssinkatu 10 - 80100 Joensuu - Finland - Tel. +358 13 120 490 - info@dhydro.com

CM 70/CM 100



TECHNICAL SPECIFICATIONS

	CM 70	CM 100
Max hose size	1 1/4" 4SH	1 1/2" 4SH
Max outside Ø	70 mm	100 mm
Blade Ø	250 mm	300 mm
Blade	Smooth (standard) Carved (option)	Carved
Suction connection	100 mm	100 mm
Standard motor	2,2 kW 400V 3-Ph	4 kW 400V 3-Ph
Different voltage versions available		
Control	Footpedal	Footpedal
Blade speed	3000 rpm	3000 rpm
Weight (kg)	100	115
Dimensions (LxWxH mm)	730 x 470 x 900	730 x 470 x 900

WWW.DHYDRO.COM

MM 51



TECHNICAL SPECIFICATIONS

Max ferrule size	85 mm
Marking height	3 mm
2 line stamp holder	Standard
Numbering wheel stamp holder	Optional
Weight (kg)	23 kg
Dimensions (LxWxH mm)	285 x 190 x 340



Character set is sold separately

STAMP HOLDERS

2-line stamp holder: 2 x 16
Characters



Numbering wheel stamp
holder: 10 characters +
3 digits wheel



WWW.DHYDRO.COM

Wahlforssinkatu 10 - 80100 Joensuu - Finland - Tel. +358 13 120 490 - info@dhydro.com

YL-20



STANDARD DIE SETS

Size	Range (mm)	Lenght
32-10	10-13	55
32-13	13-16	55
32-16	16-19	55
32-19	19-22	55
32-22	22-26	55
32-26	26-30	55
32-30	30-34	75
32-34	34-39	75
32-39	39-45	75
32-45	45-55	90

TECHNICAL SPECIFICATIONS

Max hose size	1 ¼"
With additional die sets	1 ½"
Crimping force (kN):	1700
Max crimping Ø (mm):	55
Max opening (mm):	die diameter + 26
Standard motor:	3,6 kW 400V 3-ph
Different voltage versions available	
Control	Digital control
Master dies opening/Length(mm):	124/80
Crimping range (mm):	10 – 55
Weight (kg)	200 (without oil)
Dimensions (LxWxH mm)	600 x 480 x 600
Foot pedal	Standard
Die sets	Standard
10-13-16-19-22-26-30-34-39-45	

WWW.DHYDRO.COM

Wahlforssinkatu 10 - 80100 Joensuu - Finland - Tel. +358 13 120 490 - info@dhydro.com

YL-20 S



STANDARD DIE SETS

Size	Range (mm)	Length
32-10	10-13	55
32-13	13-16	55
32-16	16-19	55
32-19	19-22	55
32-22	22-26	55
32-26	26-30	55
32-30	30-34	75
32-34	34-39	75
32-39	39-45	75
32-45	45-55	90

TECHNICAL SPECIFICATIONS

Max hose size	1 ¼"
With additional die sets	1 ½"
Crimping force (kN):	1700
Max crimping Ø (mm):	55
Max opening (mm):	die diameter + 26
Standard motor:	3,6kW 400V 3-ph
Different voltage versions available	
Control	Digital control
Master dies opening/Length(mm):	124/80
Crimping range (mm):	10 – 55
Weight (kg)	230 (without oil)
Dimensions (LxWxH mm)	600 x 480 x 1300
Quick Change-set	Standard
Foot pedal or Back stop device	Standard
Stand for machine	Standard
Die sets	Standard
10-13-16-19-22-26-30-34-39-45	

WWW.DHYDRO.COM

Wahlforssinkatu 10 - 80100 Joensuu - Finland - Tel. +358 13 120 490 - info@dhydro.com

YL-32



STANDARD DIE SETS

Size	Range (mm)	Length
32-10	10-13	55
32-13	13-16	55
32-16	16-19	55
32-19	19-22	55
32-22	22-26	55
32-26	26-30	55
32-30	30-34	75
32-34	34-39	75
32-39	39-45	75
32-45	45-52	90
32-52	52-57	90
32-57	57-64	90
32-64	64-69	100
32-69	69-79	100

TECHNICAL SPECIFICATIONS

Max hose size	2" 4 SP
Crimping force (kN):	2200
Max crimping Ø (mm):	79
Max opening (mm):	die diameter + 32
Standard motor:	3,6 kW 400V 3-ph
Different voltage versions available	
Control	Digital control
Master dies opening / Length (mm):	132/80
Crimping range (mm):	10 – 79
Weight (kg)	270 (without oil)
Dimensions (LxWxH mm)	600 x 480 x 1300
Die sets	Standard
10-13-16-19-22-26-30-34-39-45-52-57-64-69	
Quick Change-set	Standard
Foot pedal	Standard
Stand for machine	Standard

WWW.DHYDRO.COM

YL-65



STANDARD DIE SETS

Size	Range (mm)	Length
32-10	10-13	55
32-13	13-16	55
32-16	16-19	55
32-19	19-22	55
32-22	22-26	55
32-26	26-30	55
32-30	30-34	75
32-34	34-39	75
32-39	39-45	75
32-45	45-52	90
32-52	52-57	90
32-57	57-64	90
32-64	64-69	100
32-69	69-74	100
32-74	74-78	110
32-78	78-88	110

TECHNICAL SPECIFICATIONS

Max hose size	2" 4SP
Crimping force (kN):	2400
Max crimping Ø (mm):	88
Max opening (mm):	die diameter + 65
Standard motor:	5,5kW 400V 3-Ph
Different voltage versions available	
Control	Digital control
Master dies opening / Length (mm):	163/97
Crimping range (mm):	10 - 88
Weight (kg)	1200 (without oil)
Dimensions (LxWxH mm)	850 x 1000 x 1500
Die sets	Standard
10-13-16-19-22-26-30-34-39-45-52-57-64-69-74-78	
Quick Change-set	Standard
Back stop device	Standard
Foot pedal	Standard

WWW.DHYDRO.COM

Wahlforssinkatu 10 - 80100 Joensuu - Finland - Tel. +358 13 120 490 - info@dhydro.com

YL-80



STANDARD DIE SETS

Size	Range (mm)	Lenght
32-10	10-13	55
32-13	13-16	55
32-16	16-19	55
32-19	19-22	55
32-22	22-26	55
32-26	26-30	55
32-30	30-34	75
32-34	34-39	75
32-39	39-45	75
32-45	45-52	90
32-52	52-57	90
32-57	57-64	90
32-64	64-69	100
32-69	69-74	100
32-74	74-78	110
32-78	78-87	110
80-84	84-92	110
80-92	92-100	110
80-100	100-108	110
80-108	108-116	110
80-116	116-126	110

TECHNICAL SPECIFICATIONS

Max hose size	4"
Crimping force (kN):	3200
Max crimping Ø (mm):	126
Max opening (mm):	die diameter + 80
Standard motor:	5,5kW 400V 3-Ph
Different voltage versions available	
Control	Digital control
Master dies opening / Length (mm):	220/97
Crimping range (mm):	10 - 126
Weight (kg)	1350 (without oil)

Dimensions (LxWxH mm)	850 x 1000 x 1600
Die sets	Standard
10-13-16-19-22-26-30-34-39-45-52-57-64-69-74-78-84-92-100-108-116	
Quick Change-set	Standard
Back stop device	Standard
Foot pedal	Standard

WWW.DHYDRO.COM

Wahlforssinkatu 10 - 80100 Joensuu - Finland - Tel. +358 13 120 490 - info@dhydro.com

YL-125



TECHNICAL SPECIFICATIONS

Max hose size	6"
Crimping force (kN):	4000
Max crimping Ø (mm):	202
Max opening (mm):	die diameter + 125
Standard motor:	5,5kW 400V 3-Ph
Different voltage versions available	
Control	Digital control
Master dies opening / Length (mm):	335/116
Crimping range (mm):	10 - 202
Weight (kg)	3000 (without oil)

STANDARD DIE SETS

Size	Range (mm)	Lenght
32-10	10-13	55
32-13	13-16	55
32-16	16-19	55
32-19	19-22	55
32-22	22-26	55
32-26	26-30	55
32-30	30-34	75
32-34	34-39	75
32-39	39-45	75
32-45	45-52	90
32-52	52-57	90
32-57	57-64	90
32-64	64-69	100
32-69	69-74	100
32-74	74-78	110
32-78	78-87	110
125-84	84-92	116
125-92	92-100	116
125-100	100-108	116
125-108	108-116	116
125-116	116-126	116
125-126	126-136	116
125-136	136-146	116
125-146	146-156	116
125-156	156-166	116
125-166	166-178	116
125-178	178-190	116
125-190	190-202	116

Dimensions (LxWxH mm)	1050 x 1300 x 1750
Die sets	Standard
10-13-16-19-22-26-30-34-39-45-52-57-64-69-74-78-84-92-100-108-116-126-136-146-156-166-178-190	
Quick Change-set	Standard
Back stop device	Standard
Foot pedal	Standard

WWW.DHYDRO.COM

Wahlforssinkatu 10 - 80100 Joensuu - Finland - Tel. +358 13 120 490 - info@dhydro.com

YL-330



OPTIONAL DIE SETS

Size	Range (mm)	Length
125-84	84-92	116
125-92	92-100	116
125-100	100-108	116
125-108	108-116	116
125-116	116-126	116
125-126	126-136	116
125-136	136-146	116
125-146	146-156	116
125-156	156-166	116
125-166	166-178	116
125-178	178-190	116
125-190	190-202	116
330-205	205-220	220
330-220	220-235	220
330-235	235-250	220
330-250	250-270	220
330-270	270-290	220
330-290	290-305	220
330-305	305-335	220

TECHNICAL SPECIFICATIONS

Max hose size	12"
Crimping force (kN):	8300
Max crimping Ø (mm):	335
Max opening (mm):	die diameter + 155
Standard motor:	11 kW 400V 3-Ph
Different voltage versions available	
Control	Digital control
Master dies opening / Length (mm):	485/220
Crimping range (mm):	10 - 350
Weight (kg)	4500 + 500 (without oil)

WWW.DHYDRO.COM

Wahlforssinkatu 10 - 80100 Joensuu - Finland - Tel. +358 13 120 490 - info@dhydro.com

YL-SF 60



OPTIONAL DIE SETS

Size	Range (mm)	Lenght
SF60-10	10-12	55
SF60-12	12-14	55
SF60-14	14-16	55
SF60-16	16-19	55
SF60-19	19-22	55
SF60-22	22-24	55
SF60-24	24-30	55
SF60-30	30-38	55

TECHNICAL SPECIFICATIONS

Max hose size	1 ¼"
Crimping force (kN):	600
Max crimping Ø (mm):	87
Max opening (mm):	die diameter +25, +100
Standard motor:	3,6 kW 400V 3-ph
Different voltage versions available	
Control	Digital control
Crimping range (mm):	10 - 87
Weight (kg)	1190 (without oil)
Dimensions (LxWxH mm)	1032 x 1300 x 1930
Die sets	Optional
10-12-14-16-19-22-24-30	
Back stop device	Standard

WWW.DHYDRO.COM


Wahlforssinkatu 10 - 80100 Joensuu - Finland - Tel. +358 13 120 490 - info@dhydro.com

HS 50 M

SKIVING HEADS

External size	Range (mm)
3/16"	0-55
1/4"	0-55
5/16"	0-55
3/8"	0-55
1/2"	0-55
5/8"	0-55
3/4"	0-55
1"	0-55
1"	55-90
1 1/4"	0-55
1 1/4"	55-90
1 1/2"	0-55
1 1/2"	55-90
2"	50-90

Internal size	Range
3/8"	adjustable ↔
1/2"	adjustable ↔
5/8"	adjustable ↔
3/4"	adjustable ↔
1"	adjustable ↔
1 1/4"	adjustable ↔
1 1/2"	adjustable ↔
2"	adjustable ↔



Skiving heads are sold separately


TECHNICAL SPECIFICATIONS

Max hose size	2" (internal & external)
Control	Manual
Weight (kg)	2,25
Dimensions (LxWxH mm)	415 x 235 x 50

WWW.DHYDRO.COM

Wahlforssinkatu 10 - 80100 Joensuu - Finland - Tel. +358 13 120 490 - info@dhydro.com

HS 50



TECHNICAL SPECIFICATIONS

Max hose size	2" (internal & external)
Standard motor	1,1 kW 400V 3-Ph
Different voltage versions available	
Control	Footpedal
Blade speed	150 rpm
Weight (kg)	25
Dimensions (LxWxH mm)	460 x 490 x 270

SKIVING HEADS

External size	Range (mm)
3/16"	0-55
1/4"	0-55
5/16"	0-55
3/8"	0-55
1/2"	0-55
5/8"	0-55
3/4"	0-55
1"	0-55
1"	55-90
1 1/4"	0-55
1 1/4"	55-90
1 1/2"	0-55
1 1/2"	55-90
2"	50-90

Internal size	Range
3/8"	adjustable ↕↔
1/2"	adjustable ↕↔
5/8"	adjustable ↕↔
3/4"	adjustable ↕↔
1"	adjustable ↕↔
1 1/4"	adjustable ↕↔
1 1/2"	adjustable ↕↔
2"	adjustable ↕↔



Skiving heads are sold separately

WWW.DHYDRO.COM

Wahlforssinkatu 10 - 80100 Joensuu - Finland - Tel. +358 13 120 490 - info@dhydro.com

YL-NC 20



STANDARD DIE SETS

Size	Range (mm)	Lenght
NC20-12	12-14	3
NC20-14	14-16	3
NC20-16	16-19	4
NC20-19	19-22	4
NC20-22	22-26	4,5
NC20-26	26-30	4,5
NC20-30	30-34	5
NC20-34	34-39	5
NC20-39	39-45	5
NC20-45	45-52	5
NC20-52	52-57	5
NC20-57	57-66	5

TECHNICAL SPECIFICATIONS

Max hose size	1 1/4"
Crimping force (kN):	500
Max crimping Ø (mm):	66
Max opening (mm):	die diameter + 20
Standard motor:	3,6kW 400V 3-ph
Different voltage versions available	
Control	Digital control
Crimping range (mm):	4 - 66
Weight (kg)	300 (without oil)
Dimensions (LxWxH mm)	600 x 1000 x 930
Die sets	Standard
12-14-16-19-22-26-30-34-39-45-52-57	
Foot pedal	Standard

WWW.DHYDRO.COM

YL-NC 30



STANDARD DIE SETS

Size	Range (mm)	Lenght
NC20-12	12-14	3
NC20-14	14-16	3
NC20-16	16-19	4
NC20-19	19-22	4
NC20-22	22-26	4,5
NC20-26	26-30	4,5
NC20-30	30-34	5
NC20-34	34-39	5
NC20-39	39-45	5
NC20-45	45-52	5
NC20-52	52-57	5
NC20-57	57-66	5
NC30-64	64-69	5
NC30-69	69-74	5
NC30-74	74-78	5

TECHNICAL SPECIFICATIONS

Max hose size	2"
Crimping force (kN):	740
Max crimping Ø (mm):	82
Max opening (mm):	die diameter + 26
Standard motor:	3,6kW 400V 3-ph
Different voltage versions available	
Control	Digital control
Crimping range (mm):	4 - 82
Weight (kg)	340 (without oil)
Dimensions (LxWxH mm)	600 x 1000 x 930
Die sets	Standard
12-14-16-19-22-26-30-34-39-45-52-57-64-69-74	
Foot pedal	Standard

WWW.DHYDRO.COM

CR 6



TECHNICAL SPECIFICATIONS

Levels	6
Weight (kg)	75
Dimensions (LxWxH mm)	1165 x 1115 x 2050



WWW.DHYDRO.COM

Wahlforssinkatu 10 - 80100 Joensuu - Finland - Tel. +358 13 120 490 - info@dhydro.com

TECHNICAL SPECIFICATIONS

Protection pads*	4 pcs
Flexible magnet	1pc
Heavy duty Molybdenum grease	50 gr
Machine types	SM 625 - SM 25 - SM 32 - SM 38 - SM 50

(*) 8 pcs of rubber springs for SM 625 & SM 625 E

